

Стиральные машины для оборудования WD, сушильные машины TX, T, NTW, DAM, DAMC, стиральные машины SD, FX, SP, NTW, SC

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: mhi@nt-rt.ru || сайт: <http://metos.nt-rt.ru/>

Washer machine Metos

WD-12S PPE for equipment

The Metos WD-12S PPE, Personal Protective Equipment, Combi Washer is easily modified to wash entire diving equipment or individual items. The spacious washing area of the machine and its adjustable washing pressure facilitate versatile use of the appliance for cleaning the equipment of various emergency stations, water and sewage facilities, and mines. Thanks to the separate filling and emptying counters, working motion always occurs at an ergonomic height, while the need for lifting and carrying is minimised.

- Insulated design with automatic hood
- Quick adjustment of water pressure between heavily soiled equipment and smaller PPE-details
- Three programmes, adjustable up to 25 minutes with 2 intermediate rinses and 1 final rinse
- Back flow protection according to EN 1717
- Break tank including booster pump
- Cable for electrical connection L = 3m

Equipped with:

- Plastic basket
- 8-compartment basket
- Stainless steel basket
- Foldable metal shelf (internal)
- Drying agent injector

Options:

- Autostart
- Drain pump
- Stainless couplings in the final rinse (always with RO-unit)
- Operating panel left side
- Detergent pump for liquid detergent
- Extra stainless steel basket



Washer machine Metos WD-12S PPE for equipment

Item width mm	1295
Item depth mm	815
Item height mm	1694/2355
Package volume	1.994
Unit of volume	m3
Package volume	1.994 m3
Package length	134
Package width	86
Package height	173
Package unit of dimension	cm
Package dimensions (LxWxH)	134x86x173 cm
Net weight	260
Net weight	260 kg
Gross weight	280
Package weight	280 kg
Unit of weight	kg
Connection power kW	15
Fuse Size A	32
Connection voltage V	400
Number of phases	3NPE
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. height mm	440
Hot water diam.	R1/2"
Hot water flow l/min	10
Hot water min pressure kPa	20
Drain diameter	50
Drain flow l/s	3
Drain conn. height mm	109

Washer machine Metos WD-12S PPE for equipment

Sound level dB	64
Operation type	electronical
Programmability	programmable
Amount of programs	3
Insulation	insulated

Washing machine Metos WD-8 PPE for equipment with automatic

The Metos WD-8A PPE equipment washer is easily modified to wash entire diving equipment or individual items. The spacious washing area of the machine and its adjustable washing pressure facilitate versatile use of the appliance for cleaning the equipment of various emergency stations, water and sewage facilities, and mines. Thanks to the separate filling and emptying counters, working motion always occurs at an ergonomic height, while the need for lifting and carrying is minimised.

The WD-8A PPE equipment washer comes with an automatic hood lift and has three washing programmes with adjustable washing pressure, washing time, rinsing time, and rinsing temperature. A stainless steel washing basket has been designed specifically for washing diving equipment. Masks and other smaller equipment can be easily washed in plastic washing baskets or equipment trays. The washing programme starts when the hood is closed. Automatic hood lift occurs at the push of a button. The unique structure of the hood prevents steam from hitting the user's face when opening. The double-skinned hood saves energy and improves sound insulation.

The machine warns of too low temperatures and insufficient rinsing water quantity. If the rinsing water temperature falls below 85°C, the machine continues washing until the rinsing water temperature has been reached. The machine will always check the quantity of water used in the final rinse is correct and will alert if water flow is insufficient.

The deep tank of the Metos WD-8A PPE equipment washer prevents the wash water from



frothing. A deep tank together with effective filters keeps the wash water cleaner for longer. The wash pump and washing arms are self-draining prior to the final rinse, thereby preventing wash water dropping on clean equipment.

The machine's control panel displays the selected programme, temperature and remaining wash time. The control panel also displays the total number of baskets washed either daily or for the entire time it has been used. The machine will alert if the water supply is turned off or if the overflow pipe is detached. The equipment washer is easy to keep clean using the automatic cleaning programme. A robust structure and stainless steel components ensure durable and reliable operation for a number of years.

- automatic hood lift (minimum cold water pressure for hood lifting is 300 kPa)
- specially intended for washing the equipment of rescue stations, water and sewage facilities, and the mining industry
- three adjustable washing programmes, max. washing time 25 minutes (includes two intermediate rinses and the final rinse)
- washing area height 500 mm, depth 660 mm
- normal and powerful washing pressure using a single lever
- stainless steel washing arms
- pump power 1.5 kW
- boiler 9 kW
- electronic control
- sound and heat insulation
- connected to hot water supply
- basin capacity 50 litres
- basket size 500 x 500 mm

CONTENT OF DELIVERY:

- plastic washing basket
- equipment tray
- stainless steel washing basket
- rinse aid dispenser
- 2-metre power lead

EXTRAS (to be ordered separately)

- stainless steel washing basket
- roller conveyor
- equipment washer with break tank (incl. pressure boost pump)
- equipment washer with drain pump
- equipment washer with automatic start up (hood up and down with basket detector)
- equipment washer connected to the cold water supply (+ 12.9 kW boiler, 25 A) frothing. A deep tank together with effective filters keeps the wash water cleaner for longer. The wash pump and washing arms are self-draining prior to the final rinse, thereby preventing wash water dropping on clean equipment.

The machine's control panel displays the selected programme, temperature and remaining wash time. The control panel also displays the total number of baskets washed either daily or for the entire time it has been used. The machine will alert if the water supply is turned off or if the overflow pipe is detached. The equipment washer is easy to keep clean using the automatic cleaning programme. A robust structure and stainless steel components ensure durable and reliable operation for a number of years.

- automatic hood lift (minimum cold water pressure for hood lifting is 300 kPa)
- specially intended for washing the equipment of rescue stations, water and sewage facilities, and the mining industry
- three adjustable washing programmes, max. washing time 25 minutes (includes two intermediate rinses and

the final rinse)

- washing area height 500 mm, depth 660 mm
- normal and powerful washing pressure using a single lever
- stainless steel washing arms
- pump power 1.5 kW
- boiler 9 kW
- electronic control
- sound and heat insulation
- connected to hot water supply
- basin capacity 50 litres
- basket size 500 x 500 mm

CONTENT OF DELIVERY:

- plastic washing basket
- equipment tray
- stainless steel washing basket
- rinse aid dispenser
- 2-metre power lead

EXTRAS (to be ordered separately)

- stainless steel washing basket
- roller conveyor
- equipment washer with break tank (incl. pressure boost pump)
- equipment washer with drain pump
- equipment washer with automatic start up (hood up and down with basket detector)
- equipment washer connected to the cold water supply (+ 12.9 kW boiler, 25 A)

Washing machine Metos WD-8 PPE for equipment with automatic

Item width mm	872
Item depth mm	659
Item height mm	1540/2080
Package volume	1.086
Unit of volume	m3
Package volume	1.086 m3
Package length	86
Package width	76.5
Package height	165
Package unit of dimension	cm
Package dimensions (LxWxH)	86x76.5x165 cm
Net weight	130
Net weight	130 kg
Gross weight	155
Package weight	155 kg
Unit of weight	kg
Connection power kW	10.5
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	45
Electrical conn. diam. mm	2,5
Electrical cable length mm	3000
Hot water diam.	R1/2"
Hot water thread	Internal thread
Hot water flow l/min	18
Hot water min pressure kPa	300
Hot water max pressure kPa	500

Washing machine Metos WD-8 PPE for equipment with automatic

Hot water conn. inlet	Right;Behind;Bottom
Hot water conn. height mm	265
Remarks (hot water)	avstäng.kran på vattenledning
Drain diameter	50
Drain flow l/s	3
Drain conn. height mm	215
Floor drain needed	Yes
Remarks (drain)	2 m drain hose included
Sound level dB	65
Heat load sensitive W	1700
Heat load latent W	600

Washing machine Metos

WD-8 PPE for equipment

The Metos WD-8 PPE equipment washer is easily modified to wash entire diving equipment or individual items. The spacious washing area of the machine and its adjustable washing pressure facilitate versatile use of the appliance for cleaning the equipment of various emergency stations, water and sewage facilities, and mines. Thanks to the separate filling and emptying counters, working motion always occurs at an ergonomic height, while the need for lifting and carrying is minimised.

This equipment washer comes with an automatic hood lift and has three washing programmes with adjustable washing pressure, washing time, rinsing time, and rinsing temperature. A stainless steel washing basket has been designed specifically for washing diving equipment. Masks and other smaller equipment can be easily washed in plastic washing baskets or equipment trays. The washing programme starts when the hood is closed. The unique structure of the hood prevents steam from hitting the user's face when opening. The double-skinned hood saves energy and improves sound insulation.

The machine warns of too low temperatures and insufficient rinsing water quantity. If the rinsing water temperature falls below 85°C, the machine continues washing until the rinsing water temperature has been reached. The machine will always check the quantity of water used in the final rinse is correct and will alert if water flow is insufficient.

The deep tank of the Metos WD-8 PPE equipment washer prevents the wash water from frothing. A deep tank together with effective filters keeps the



wash water cleaner for longer. The wash pump and washing arms are self-draining prior to the final rinse, thereby preventing wash water dropping on clean equipment.

The machine's control panel displays the selected programme, temperature and remaining wash time. The control panel also displays the total number of baskets washed either daily or for the entire time it has been used. The machine will alert if the water supply is turned off or if the overflow pipe is detached. The equipment washer is easy to keep clean using the automatic cleaning programme. A robust structure and stainless steel components ensure durable and reliable operation for a number of years.

- specially intended for washing the equipment of rescue stations, water and sewage facilities, and the mining industry
- three adjustable washing programmes, max. washing time 25 minutes (includes two intermediate rinses and the final rinse)
- washing area height 500 mm, depth 660 mm
- normal and powerful washing pressure using a single lever
- stainless steel washing arms
- pump power 1.5 kW
- boiler 9 kW
- electronic control
- sound and heat insulation
- connected to hot water supply
- basin capacity 50 litres
- basket size 500 x 500 mm

CONTENT OF DELIVERY:

- plastic washing basket
- equipment tray
- stainless steel washing basket
- rinse aid dispenser
- 2-metre power lead

EXTRAS (to be ordered separately)

- stainless steel washing basket
 - roller conveyor
 - equipment washer with break tank (incl. pressure boost pump)
 - equipment washer with drain pump
 - equipment washer with automatic hood lift
 - equipment washer with automatic start up (hood up and down with basket detector)
 - equipment washer connected to the cold water supply (+ 12.9 kW boiler, 25 A) wash water cleaner for longer.
- The wash pump and washing arms are self-draining prior to the final rinse, thereby preventing wash water dropping on clean equipment.

The machine's control panel displays the selected programme, temperature and remaining wash time. The control panel also displays the total number of baskets washed either daily or for the entire time it has been used. The machine will alert if the water supply is turned off or if the overflow pipe is detached. The equipment washer is easy to keep clean using the automatic cleaning programme. A robust structure and stainless steel components ensure durable and reliable operation for a number of years.

- specially intended for washing the equipment of rescue stations, water and sewage facilities, and the mining industry
- three adjustable washing programmes, max. washing time 25 minutes (includes two intermediate rinses and the final rinse)
- washing area height 500 mm, depth 660 mm

- normal and powerful washing pressure using a single lever
- stainless steel washing arms
- pump power 1.5 kW
- boiler 9 kW
- electronic control
- sound and heat insulation
- connected to hot water supply
- basin capacity 50 litres
- basket size 500 x 500 mm

CONTENT OF DELIVERY:

- plastic washing basket
- equipment tray
- stainless steel washing basket
- rinse aid dispenser
- 2-metre power lead

EXTRAS (to be ordered separately)

- stainless steel washing basket
- roller conveyor
- equipment washer with break tank (incl. pressure boost pump)
- equipment washer with drain pump
- equipment washer with automatic hood lift
- equipment washer with automatic start up (hood up and down with basket detector)
- equipment washer connected to the cold water supply (+ 12.9 kW boiler, 25 A)

Washing machine Metos WD-8 PPE for equipment

Product capacity	30 baskets / hour
Item width mm	750/844
Item depth mm	659
Item height mm	1540/2080
Package volume	1.086
Unit of volume	m3
Package volume	1.086 m3
Package length	86
Package width	76.5
Package height	165
Package unit of dimension	cm
Package dimensions (LxWxH)	86x76.5x165 cm
Net weight	125
Net weight	125 kg
Gross weight	155
Package weight	155 kg
Unit of weight	kg
Connection power kW	10.1
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	45
Electrical conn. diam. mm	2,5
Electrical cable length mm	3000
Water hardness °dH	5
Remarks (cold water)	shut off cock on incoming pipe
Hot water diam.	R1/2"
Hot water thread	Internal thread

Washing machine Metos WD-8 PPE for equipment

Hot water flow l/min	18
Hot water min pressure kPa	180
Hot water max pressure kPa	300
Hot water conn. inlet	Right;Behind;Bottom
Hot water conn. height mm	265
Drain diameter	50
Drain flow l/s	3
Drain conn. height mm	215
Floor drain needed	Yes
Remarks (drain)	2 m drain hose included
Sound level dB	65
Heat load sensitive W	1700
Heat load latent W	600
Operation type	electronical
Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos T11 HP FCT with heat pump

Dryer with heat pump. Standard stainless steel Ø 760 mm drum, volume 250 litres

- drying average 126 g/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large glass door
- Ø 600 mm opening for easy loading and unloading
- self cleaning lint screen
- full control programmer (FCT)
- sliding base frame



Tumble dryer Metos T11 HP FCT with heat pump

Product capacity	11 kg
Item width mm	795
Item depth mm	1525
Item height mm	1680
Package volume	2.35
Unit of volume	m3
Package volume	2.35 m3
Package length	85.5
Package width	154
Package height	178.5
Package unit of dimension	cm
Package dimensions (LxWxH)	85.5x154x178.5 cm
Net weight	350
Net weight	350 kg
Gross weight	385
Package weight	385 kg
Unit of weight	kg
Connection power kW	4.3
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos TX 9 HP (with heat pump)

Industrial tumble dryer Metos TX9 HP, with heat pump

- standard stainless steel Ø 670 mm drum, volume 195 litres
- anthracite grey skin plate
- inox top panel
- ECT easy-to-use microprocessor
- DimpleDry™ with innovative bulged drum
- axial air flow
- 210° door opening for easy loading and unloading
- heat pump unit easy accessible from the front
- intuitive control with simple selection and 3 programs
- triple filtration system
- optimized 0.65m² footprint to install anywhere

Options

- stainless steel front panel
- reverse drum
- coin operated version



Tumble dryer Metos TX 9 HP (with heat pump)

Product capacity	9 kg
Item width mm	710
Item depth mm	925
Item height mm	1725
Package volume	1.342
Unit of volume	m3
Package volume	1.342 m3
Package length	76
Package width	97
Package height	182
Package unit of dimension	cm
Package dimensions (LxWxH)	76x97x182 cm
Net weight	192
Net weight	192 kg
Gross weight	208
Package weight	208 kg
Unit of weight	kg
Connection power kW	2
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	43
Type of electrical connection	Semifixed
Cold water diam.	2x1"
Drain diameter	16 mm
Sound level dB	54
Operation type	electronical
Drum material	stainless steel

Tumble dryer Metos TX 9 HP (with heat pump)

Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos T13 HP FCT with heat pump

Dryer with heat pump. Standard stainless steel Ø 760 mm drum, volume 285 litres

- drying average 120 g/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large glass door
- Ø 600 mm opening for easy loading and unloading
- self cleaning lint screen
- full control programmer (FCT)
- sliding base frame



Tumble dryer Metos T13 HP FCT with heat pump

Product capacity	13 kg
Item width mm	795
Item depth mm	1615
Item height mm	1680
Package volume	2.495
Unit of volume	m ³
Package volume	2.495 m ³
Package length	85.5
Package width	163.5
Package height	178.5
Package unit of dimension	cm
Package dimensions (LxWxH)	85.5x163.5x178.5 cm
Net weight	360
Net weight	360 kg
Gross weight	400
Package weight	400 kg
Unit of weight	kg
Connection power kW	4.3
Fuse Size A	10
Connection voltage V	380-415
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	43
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos T9 HP FCT with heat pump

Dryer with heat pump. Standard stainless steel Ø 760 mm drum, volume 195 litres

- drying average 122 g/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large glass door
- Ø 600 mm opening for easy loading and unloading
- self cleaning lint screen
- full control programmer (FCT)
- sliding base frame



Tumble dryer Metos T9 HP FCT with heat pump

Product capacity	9 kg
Item width mm	795
Item depth mm	1275
Item height mm	1465
Package volume	1.844
Unit of volume	m3
Package volume	1.844 m3
Package length	88
Package width	133.5
Package height	157
Package unit of dimension	cm
Package dimensions (LxWxH)	88x133.5x157 cm
Net weight	290
Net weight	290 kg
Gross weight	305
Package weight	305 kg
Unit of weight	kg
Connection power kW	4.2
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos T16 HP FCT with heat pump

Dryer with heat pump. Standard stainless steel Ø 760 mm drum, volume 345 litres

- drying average 120 g/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large glass door
- Ø 600 mm opening for easy loading and unloading
- self cleaning lint screen
- full control programmer (FCT)
- sliding base frame



Tumble dryer Metos T16 HP FCT with heat pump

Product capacity	16 kg
Item width mm	795
Item depth mm	1735
Item height mm	1680
Package volume	2.671
Unit of volume	m3
Package volume	2.671 m3
Package length	85.5
Package width	175
Package height	178.5
Package unit of dimension	cm
Package dimensions (LxWxH)	85.5x175x178.5 cm
Net weight	375
Net weight	375 kg
Gross weight	400
Package weight	400 kg
Unit of weight	kg
Connection power kW	4.3
Fuse Size A	10
Connection voltage V	380-415
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos T24

Standard stainless steel Ø 930 mm drum, volume 530 litres.

Stainless steel front

- ECT easy-to-use microprocessor
- air flow 950 m³/h
- drying average 0,384 l/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large door Ø 810 mm opening for easy loading and unloading
- self cleaning lintscreen
- to be connected to the exhaust chimney



Tumble dryer Metos T24

Product capacity	24kg
Item width mm	965
Item depth mm	1270
Item height mm	1975
Package volume	2.855
Unit of volume	m3
Package volume	2.855 m3
Package length	104
Package width	132
Package height	208
Package unit of dimension	cm
Package dimensions (LxWxH)	104x132x208 cm
Net weight	275
Net weight	275 kg
Gross weight	300
Package weight	300 kg
Unit of weight	kg
Connection power kW	30.7
Fuse Size A	50
Connection voltage V	400
Number of phases	3PE
Frequency Hz	50
Protection rating (IP)	43
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	3
Insulation	insulated

Tumble dryer Metos T11

Standard stainless steel Ø 760 mm drum, volume 250 litres.

Stainless steel front

- ECT easy-to-use microprocessor
- air flow 520 m³/h
- drying average 0,190 g/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large door Ø 600 mm opening for easy loading and unloading
- self cleaning lintscreen
- to be connected to the exhaust chimney



Tumble dryer Metos T11

Product capacity	11 kg
Item width mm	795
Item depth mm	1070
Item height mm	1680
Package volume	1.693
Unit of volume	m3
Package volume	1.693 m3
Package length	110
Package width	86
Package height	179
Package unit of dimension	cm
Package dimensions (LxWxH)	110x86x179 cm
Net weight	230
Net weight	230 kg
Gross weight	240
Package weight	240 kg
Unit of weight	kg
Connection power kW	14.2
Fuse Size A	25
Connection voltage V	400
Number of phases	3PE
Frequency Hz	50
Protection rating (IP)	43
Type of electrical connection	Semifixed
Remarks (electrical)	Exhaust 200 mm
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs

Tumble dryer Metos T35

Standard stainless steel Ø 930 mm drum, volume 680 litres.

Stainless steel front

- ECT easy-to-use microprocessor
- air flow 1200 m³/h
- drying average 0,560 l/min.
- short drying time
- maximal heat transfer
- low energy consumption
- large door Ø 810 mm opening for easy loading and unloading
- self cleaning lintscreen
- to be connected to the exhaust chimney



Tumble dryer Metos T35

Product capacity	35 kg
Item width mm	965
Item depth mm	1490
Item height mm	1975
Package volume	3.331
Unit of volume	m3
Package volume	3.331 m3
Package length	104
Package width	154
Package height	208
Package unit of dimension	cm
Package dimensions (LxWxH)	104x154x208 cm
Net weight	305
Net weight	305 kg
Gross weight	330
Package weight	330 kg
Unit of weight	kg
Connection power kW	36.7
Fuse Size A	63
Connection voltage V	400
Number of phases	3PE
Frequency Hz	50
Protection rating (IP)	43
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	3
Insulation	insulated

CODE: MG4160593

Stacked Frontload Washer and Dryer Metos NTW10

Tumble dryer stacked at the factory on top of the washer extractor. The free standing unit saves floor space.

€10,394.00

ON ORDER

Compare

Add to cart

Full description

Technical specifications

Attachments

Tumble dryer stacked at the factory on top of the washer extractor. The free standing unit saves floor space.

Washer extractor:

- extraction speed 1200 rpm
- stainless steel drum and tub
- soap hopper at the front with four compartments
- six wash programs
- wide door opening for easy loading and unloading
- space saving when dryer placed on top
- drum volume 96,8 litres

Tumble dryer vented:

- galvanized steel cylinder
- drum size 198 litres
- oversized lint filter located in front for easy cleaning
- powerful exhaust blower assures short drying times and low operating costs
- wide door opening for easy loading and unloading
- 4 drying programs

GENERAL

Description	Stacked Frontload Washer and Dryer Metos NTW10
-------------	--

DIMENSIONS AND CAPACITY

Product capacity	10,5kg/10,5kg
Item width mm	683
Item depth mm	704
Item height mm	1986
Package volume	1.333 m3
Package dimensions (LxWxH)	76x86x204 cm
Net weight	177 kg
Package weight	193 kg

TECHNICAL INFORMATION

Connection power kW	5.3
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Remarks (electrical)	can be field conv. to 230/50/3
Cold water diam.	3/4"
Cold water flow l/min	10
Cold water min pressure kPa	138
Cold water conn. height mm	813
Hot water diam.	3/4"
Hot water flow l/min	10
Hot water min pressure kPa	138
Hot water conn. height mm	813
Drain diameter	47
Drain conn. height mm	104

FEATURES

Operation type	electronical
Programmability	ready programs,programmable
Amount of programs	6

INSTALLATION

Installation	free standing
G forces	440

Dryer Metos DAM7 HP 230V/50Hz/1 with heat pump

Compact Tumble dryer with heat pump Metos DAM7 HP is easy-to-use and effective with short drying cycles.

- Titanium grey cabinet
- Stainless steel drum
- Drum dimensions Ø571 x 476 mm
- Drum volume 117 L
- Large door opening (Ø 45cm)
- Electronic front control
- Easy to use timer with color display
- Heat pump heating



Dryer Metos DAM7 HP 230V/50Hz/1 with heat pump

Product capacity	7 kg
Item width mm	595
Item depth mm	654
Item height mm	850-865
Package volume	0.43
Unit of volume	m3
Package volume	0.43 m3
Package length	73
Package width	64
Package height	92
Package unit of dimension	cm
Package dimensions (LxWxH)	73x64x92 cm
Net weight	40
Net weight	40 kg
Gross weight	45
Package weight	45 kg
Unit of weight	kg
Connection power kW	0.9
Fuse Size A	10
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	17
Insulation	insulated

Tumble dryer Metos DAMC7 with condens unitDryer Metos DAM7

Compact Dryer

- Condense model
- Capacity 6,5 kg
- Titanium grey cabinet
- Stainless steel drum
- Drum dimensions Ø571 x 476 mm
- Drum volume 117 L
- Large door opening (Ø 45cm)
- Electronic front control
- Easy to use timer with color display



Tumble dryer Metos DAMC7 with condens unitDryer Metos DAM7

Product capacity	6,5 kg
Item width mm	595
Item depth mm	654
Item height mm	850-865
Package volume	0.43
Unit of volume	m3
Package volume	0.43 m3
Package length	73
Package width	64
Package height	92
Package unit of dimension	cm
Package dimensions (LxWxH)	73x64x92 cm
Net weight	45
Net weight	45 kg
Gross weight	49.4
Package weight	49.4 kg
Unit of weight	kg
Connection power kW	2.5
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	17
Insulation	insulated

Tumble dryer Metos SD10 vented

Galvanized steel 198 litres cylinder. Solid door

- oversized lint filter located in front for easy cleaning
- powerful exhaust blower assures short drying times and low operating costs
- wide door opening of 180° for easy loading and unloading
- 4 drying programs
- LED indication of the status of the program
- time remaining countdown
- top, front and side panels in anthracite gray
- must connect to exhaust chimney



Tumble dryer Metos SD10 vented

Product capacity	10 kg
Item width mm	683
Item depth mm	711
Item height mm	1027
Package volume	0.721
Unit of volume	m3
Package volume	0.721 m3
Package length	74
Package width	84
Package height	116
Package unit of dimension	cm
Package dimensions (LxWxH)	74x84x116 cm
Net weight	68
Net weight	68 kg
Gross weight	73
Package weight	73 kg
Unit of weight	kg
Connection power kW	5.3
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	X4
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	4
Insulation	insulated

Washer extractor Metos SP10V with drain valve and readiness for detergent dispenser

Extraction speed 1200 rpm. Stainless steel look

- stainless steel drum and tub
- soap hopper at the front with four compartments
- time remaining countdown
- six wash programs
- LED indication of the program status
- door opens 180° for easy loading and unloading
- space saving when dryer placed on top
- drum volume 96,8 litres
- drain valve
- readiness to connect to an external detergent dispenser



Washer extractor Metos SP10V with drain valve and readiness for detergent dispenser

Product capacity	10 kg
Item width mm	683
Item depth mm	704
Item height mm	1027
Package volume	0.721
Unit of volume	m ³
Package volume	0.721 m ³
Package length	74
Package width	84
Package height	116
Package unit of dimension	cm
Package dimensions (LxWxH)	74x84x116 cm
Net weight	113
Net weight	113 kg
Gross weight	122
Package weight	122 kg
Unit of weight	kg
Connection power kW	4.8
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	X4
Remarks (electrical)	re-wireable to 230V 1PE
Power type	electric
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	6

Washer extractor Metos SP10V with drain valve and readiness for detergent dispenser

Insulation	insulated
------------	-----------

Washer extractor Metos FX80

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 530 mm drum
- wash speed 49 rpm
- extraction: 1165 rpm
- X control - easy to use microprocessor with 15 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX80

Product capacity	8 kg
Item width mm	710
Item depth mm	790
Item height mm	1115
Package volume	0.784
Unit of volume	m3
Package volume	0.784 m3
Package length	75
Package width	84
Package height	124.5
Package unit of dimension	cm
Package dimensions (LxWxH)	75x84x124.5 cm
Net weight	185
Net weight	185 kg
Gross weight	200
Package weight	200 kg
Unit of weight	kg
Connection power kW	6
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1010
Remarks (electrical)	Heating power 6kW
Cold water diam.	3/4"
Cold water flow l/min	20

Washer extractor Metos FX80

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1010
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Hot water conn. height mm	920
Drain conn. inlet	Behind;Right
Drain conn. height mm	88
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos FX240

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 750 mm drum, volume 240 litres
- wash speed 42 rpm
- extraction: 980 rpm
- X control Plus - programmable up to 99 programs, with 20 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX240

Product capacity	24 kg
Item width mm	970
Item depth mm	1105
Item height mm	1410
Package volume	1.827
Unit of volume	m3
Package volume	1.827 m3
Package length	102.5
Package width	115
Package height	155
Package unit of dimension	cm
Package dimensions (LxWxH)	102.5x115x155 cm
Net weight	430
Net weight	430 kg
Gross weight	450
Package weight	450 kg
Unit of weight	kg
Connection power kW	18
Fuse Size A	32
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1297,5
Remarks (electrical)	Heating power 18kW
Cold water diam.	3/4"
Cold water flow l/min	35

Washer extractor Metos FX240

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1297
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Drain flow l/s	3
Drain conn. inlet	Behind;Right
Drain conn. height mm	109
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos FX180

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 750 mm drum, volume 180 litres
- wash speed 42 rpm
- extraction: 980 rpm
- X control Plus - programmable up to 99 programs, with 20 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX180

Product capacity	18 kg
Item width mm	970
Item depth mm	970
Item height mm	1410
Package volume	1.613
Unit of volume	m3
Package volume	1.613 m3
Package length	102.5
Package width	101.5
Package height	155
Package unit of dimension	cm
Package dimensions (LxWxH)	102.5x101.5x155 cm
Net weight	380
Net weight	380 kg
Gross weight	395
Package weight	395 kg
Unit of weight	kg
Connection power kW	12
Fuse Size A	25
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1297,5
Remarks (electrical)	Heating power 12kW
Cold water diam.	3/4"
Cold water flow l/min	35

Washer extractor Metos FX180

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1297
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Drain flow l/s	3
Drain conn. inlet	Behind;Right
Drain conn. height mm	109
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos FX105

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 620 mm drum, volume 105 litres
- wash speed 49 rpm
- extraction: 1075 rpm
- X control - easy to use microprocessor with 15 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX105

Product capacity	11 kg
Item width mm	795
Item depth mm	795
Item height mm	1225
Package volume	1.106
Unit of volume	m3
Package volume	1.106 m3
Package length	83.5
Package width	98.5
Package height	134.5
Package unit of dimension	cm
Package dimensions (LxWxH)	83.5x98.5x134.5 cm
Net weight	255
Net weight	255 kg
Gross weight	275
Package weight	275 kg
Unit of weight	kg
Connection power kW	9
Fuse Size A	20
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1120
Remarks (electrical)	Heating power 9kW
Cold water diam.	3/4"
Cold water flow l/min	20

Washer extractor Metos FX105

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1030
Remarks (cold water)	water consumption 7,2 l/kg
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Drain conn. inlet	Behind;Right
Drain conn. height mm	88
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos FX280

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 750 mm drum, volume 280 litres
- wash speed 42 rpm
- extraction: 915 rpm
- X control Plus - programmable up to 99 programs, with 20 pre-set programs
- spin 350 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX280

Product capacity	28 kg
Item width mm	970
Item depth mm	1185
Item height mm	1410
Package volume	1.946
Unit of volume	m3
Package volume	1.946 m3
Package length	102.5
Package width	122.5
Package height	155
Package unit of dimension	cm
Package dimensions (LxWxH)	102.5x122.5x155 cm
Net weight	495
Net weight	495 kg
Gross weight	515
Package weight	515 kg
Unit of weight	kg
Connection power kW	22
Fuse Size A	50
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1305
Remarks (electrical)	Heating power 21,9kW
Cold water diam.	3/4"
Cold water flow l/min	35

Washer extractor Metos FX280

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1305
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Drain flow l/s	3
Drain conn. inlet	Behind;Right
Drain conn. height mm	109
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos FX65

- free standing, high spin
- stainless steel top panel and anthracite grey front and side panel
- stainless steel drum and tub
- soap hopper at the front
- extract G-force 400
- X control- easy to use microprocessor: 15 pre-set programs
- large drain valve(Ø76mm)
- easy access to all vital parts from the front
- large door opening for easy loading and unloading
- low water and energy consumption

Accessories(not included in the delivery):

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX65

Product capacity	6,5 kg
Item width mm	710
Item depth mm	740
Item height mm	1115
Package volume	0.784
Unit of volume	m3
Package volume	0.784 m3
Package length	75
Package width	84
Package height	124.5
Package unit of dimension	cm
Package dimensions (LxWxH)	75x84x124.5 cm
Net weight	170
Net weight	170 kg
Gross weight	180
Package weight	180 kg
Unit of weight	kg
Connection power kW	6.7
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1010
Remarks (electrical)	Heating power 6kW
Cold water diam.	3/4"
Cold water flow l/min	20

Washer extractor Metos FX65

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1010
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Hot water conn. height mm	920
Drain conn. inlet	Behind;Right
Drain conn. height mm	88
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos FX135

Freestanding washer with stainless steel top panel and anthracite grey front and side panel. Large door opening Ø 410 mm for easy loading and unloading

- stainless steel Ø 620 mm drum, volume 135 litres
- wash speed 49 rpm
- extraction: 1075 rpm
- X control - easy to use microprocessor with 15 pre-set programs
- spin 400 G-factor
- easy access to all vital parts from the front
- patented soap hopper
- large drain valve (Ø76 mm)
- frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

Accessories:

- plinth 135 mm
- plinth 200 mm



Washer extractor Metos FX135

Product capacity	14 kg
Item width mm	795
Item depth mm	945
Item height mm	1225
Package volume	1.106
Unit of volume	m3
Package volume	1.106 m3
Package length	83.5
Package width	98.5
Package height	134.5
Package unit of dimension	cm
Package dimensions (LxWxH)	83.5x98.5x134.5 cm
Net weight	255
Net weight	255 kg
Gross weight	275
Package weight	275 kg
Unit of weight	kg
Connection power kW	12
Fuse Size A	25
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. inlet	Top;Behind
Electrical conn. height mm	1120
Remarks (electrical)	Heating power 12kW
Cold water diam.	3/4"
Cold water flow l/min	20

Washer extractor Metos FX135

Cold water min pressure kPa	100
Cold water max pressure kPa	800
Cold water conn. inlet	Top;Behind
Cold water conn. height mm	1030
Remarks (cold water)	water consumption 7,2 l/kg
Hot water diam.	3/4"
Hot water flow l/min	20
Hot water conn. inlet	Top;Behind
Drain conn. inlet	Behind;Right
Drain conn. height mm	88
Floor drain needed	Yes
Sound level dB	65
Type	electric
Operation type	electronical
Hinge location	right
Drum material	stainless steel
Programmability	ready programs
Amount of programs	15
Insulation	insulated
Drain pump	No

Washer extractor Metos SP10P DDE with drain pump and readine

Extraction speed 1200 rpm. Stainless steel look

- stainless steel drum and tub
- soap hopper at the front with four compartments
- time remaining countdown
- six wash programs
- LED indication of the program status
- door opens 180° for easy loading and unloading
- space saving when dryer placed on top
- drum volume 96,8 litres
- drain pump
- readiness to connect to an external detergent dispenser



Washer extractor Metos SP10P DDE with drain pump and readine

Product capacity	10 kg
Item width mm	683
Item depth mm	704
Item height mm	1027
Package volume	0.721
Unit of volume	m3
Package volume	0.721 m3
Package length	74
Package width	84
Package height	116
Package unit of dimension	cm
Package dimensions (LxWxH)	74x84x116 cm
Net weight	113
Net weight	113 kg
Gross weight	122
Package weight	122 kg
Unit of weight	kg
Connection power kW	4.8
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Protection rating (IP)	X4
Remarks (electrical)	re-wireable to 230V 1PE
Operation type	electronical
Drum material	stainless steel
Programmability	ready programs
Amount of programs	6
Insulation	insulated

CODE: MG4160593

Stacked Frontload Washer and Dryer Metos NTW10

Tumble dryer stacked at the factory on top of the washer extractor. The free standing unit saves floor space.

€10,394.00

ON ORDER

Compare

Add to cart



Full description

Technical specifications

Attachments

Tumble dryer stacked at the factory on top of the washer extractor. The free standing unit saves floor space.

Washer extractor:

- extraction speed 1200 rpm
- stainless steel drum and tub
- soap hopper at the front with four compartments
- six wash programs
- wide door opening for easy loading and unloading
- space saving when dryer placed on top
- drum volume 96,8 litres

Tumble dryer vented:

- galvanized steel cylinder
- drum size 198 litres
- oversized lint filter located in front for easy cleaning
- powerful exhaust blower assures short drying times and low operating costs
- wide door opening for easy loading and unloading
- 4 drying programs

GENERAL

Description	Stacked Frontload Washer and Dryer Metos NTW10
-------------	--

DIMENSIONS AND CAPACITY

Product capacity	10,5kg/10,5kg
Item width mm	683
Item depth mm	704
Item height mm	1986
Package volume	1.333 m3
Package dimensions (LxWxH)	76x86x204 cm
Net weight	177 kg
Package weight	193 kg

TECHNICAL INFORMATION

Connection power kW	5.3
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Remarks (electrical)	can be field conv. to 230/50/3
Cold water diam.	3/4"
Cold water flow l/min	10
Cold water min pressure kPa	138
Cold water conn. height mm	813
Hot water diam.	3/4"
Hot water flow l/min	10
Hot water min pressure kPa	138
Hot water conn. height mm	813
Drain diameter	47
Drain conn. height mm	104

FEATURES

Operation type	electronical
Programmability	ready programs,programmable
Amount of programs	6

INSTALLATION

Installation	free standing
G forces	440

Washer extractor Metos SC70V with valve drain

Capacity 6,5 kg. Extraction speed 1400 rpm

- Titanium grey cabinet
- Stainless steel drum and tub
- Easy to use timer with color Display
- Available in 25 languages
- Up to 50 programs, including mop and medical programs
- Soap hopper at the front
- Matching dryer available - space saving when placed on top
- Drain valve

Options:

- Wi-fi connectivity
- Drain pump
- Liquid soap pumps



Washer extractor Metos SC70V with valve drain

Product capacity	7 kg
Item width mm	595
Item depth mm	591
Item height mm	845-865
Package volume	0.389
Unit of volume	m3
Package volume	0.389 m3
Package length	92
Package width	66
Package height	64
Package unit of dimension	cm
Package dimensions (LxWxH)	92x66x64 cm
Net weight	77
Net weight	77 kg
Gross weight	80
Package weight	80 kg
Unit of weight	kg
Connection power kW	3.2
Fuse Size A	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Remarks (electrical)	re-wireable to 230V/1PE/50Hz
Cold water diam.	3/4"
Operation type	electronical
Features	Available in 25 languages
Drum material	stainless steel
Programmability	ready programs

Washer extractor Metos SC70V with valve drain

Amount of programs	50
Insulation	insulated



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижегород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: mhi@nt-rt.ru || сайт: <http://metos.nt-rt.ru/>